



# Contour Series™ C-5 Wall & Soffit Panel

4566 RIDGE DRIVE NE  
SALEM, OR 97301

SECTION PROPERTIES								ALLOWABLE UNIFORM LOADS, psf For various fastener spacings (i.e. span values)																	
Ga.	Width in.	Yield ksi	Weight psf	Top in Compression		Bottom in Compression		Inward Load										Outward Load							
				$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'		
26	12	80	1.59	0.1106	0.1045	0.1262	0.1479	946.6	657.3	482.9	369.8	292.2	236.6	73.0	59.2	668.8	464.4	341.2	261.3	206.4	167.2	51.6	41.8		
24	12	50	2.02	0.1746	0.1793	0.1817	0.2269	907.6	630.3	464.1	354.5	280.1	226.9	70.0	56.7	717.2	498.1	365.9	280.2	221.4	179.3	55.3	44.8		
22	12	50	2.37	0.2090	0.2264	0.2130	0.2805	1122.0	779.2	572.5	438.3	346.3	280.5	86.6	70.1	905.6	628.9	462.0	353.8	279.5	226.4	69.9	56.6		
20	12	33	2.88	0.2830	0.3239	0.2860	0.3508	935.5	649.6	477.3	365.4	288.7	233.9	72.2	58.5	863.7	599.8	440.7	337.4	266.6	215.9	66.7	54.0		

- Theoretical section properties have been calculated per AISI 2012 North American Specification for the Design of Cold-Formed Steel Structural Member.  $I_{xx}$  and  $S_{xx}$  are effective section properties for deflection and bending.
- Allowable load is calculated in accordance with AISI 2012 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- Allowable load does not address web crippling, fasteners, connection strength or support material.
- Panel weight is not considered.
- Load/Span values are based on theoretical computations and not load testing.
- Deflection is not considered.
- Allowable loads do not include a 1/3 stress increase for wind.

SECTION PROPERTIES								ALLOWABLE UNIFORM LOADS, psf For various fastener spacings (i.e. span values)																	
Ga.	Width in.	Yield ksi	Weight psf	Top in Compression		Bottom in Compression		Inward Load										Outward Load							
				$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'		
26	12	80	1.59	0.1106	0.1045	0.1262	0.1479	946.6	657.3	482.9	369.8	292.2	233.0	40.0	29.1	668.8	464.4	341.2	261.3	206.4	167.2	45.6	33.2		
24	12	50	2.02	0.1746	0.1793	0.1817	0.2269	907.6	630.3	463.1	354.5	280.1	226.9	63.1	46.0	717.2	498.1	365.9	280.2	221.4	179.3	55.3	44.8		
22	12	50	2.37	0.2090	0.2264	0.2130	0.2805	1122.0	779.2	572.5	438.3	346.3	280.5	75.5	55.0	905.6	628.9	462.0	353.8	279.5	226.4	69.9	56.1		
20	12	33	2.11	0.2830	0.3239	0.2860	0.3508	935.5	649.6	477.3	365.4	288.7	233.9	72.2	58.5	863.7	599.8	440.7	337.4	266.6	215.9	66.7	54.0		

- Theoretical section properties have been calculated per AISI 2012 North American Specification for the Design of Cold-Formed Steel Structural Member.  $I_{xx}$  and  $S_{xx}$  are effective section properties for deflection and bending.
- Allowable load is calculated in accordance with AISI 2012 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- Allowable load does not address web crippling, fasteners, connection strength or support material.
- Panel weight is not considered.
- Load/Span values are based on theoretical computations and not load testing.
- Deflection consideration is limited by a maximum deflection ratio of  $L/120$  of span.
- Allowable loads do not include a 1/3 stress increase for wind.

SECTION PROPERTIES								ALLOWABLE UNIFORM LOADS, psf For various fastener spacings (i.e. span values)																	
Ga.	Width in.	Yield ksi	Weight psf	Top in Compression		Bottom in Compression		Inward Load										Outward Load							
				$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	$I_{xx}$ in <sup>4</sup> /ft.	$S_{xx}$ in <sup>3</sup> /ft.	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'	2.5'	3'	3.5'	4'	4.5'	5'	9'	10'		
26	12	80	1.59	0.1106	0.1045	0.1262	0.1479	946.6	657.3	452.8	303.4	213.1	155.3	26.6	19.4	668.8	464.4	341.2	261.3	206.4	167.2	30.4	22.2		
24	12	50	2.02	0.1746	0.1793	0.1817	0.2269	907.6	630.3	463.1	354.5	280.1	226.9	42.0	30.7	717.2	498.1	365.9	280.2	221.4	179.3	43.8	31.9		
22	12	50	2.37	0.2090	0.2264	0.2130	0.2805	1122.0	779.2	572.5	438.3	346.3	280.5	50.3	36.7	905.6	628.9	462.0	353.8	279.5	226.4	51.3	37.4		
20	12	33	2.11	0.2830	0.3239	0.2860	0.3508	935.5	649.6	477.3	365.4	288.7	233.9	68.2	49.7	863.7	599.8	440.7	337.4	266.6	215.9	66.7	50.2		

- Theoretical section properties have been calculated per AISI 2012 North American Specification for the Design of Cold-Formed Steel Structural Member.  $I_{xx}$  and  $S_{xx}$  are effective section properties for deflection and bending.
- Allowable load is calculated in accordance with AISI 2012 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- Allowable load does not address web crippling, fasteners, connection strength or support material.
- Panel weight is not considered.
- Load/Span values are based on theoretical computations and not load testing.
- Deflection consideration is limited by a maximum deflection ratio of  $L/180$  of span.
- Allowable loads do not include a 1/3 stress increase for wind.



**EXPIRES 09-16-2018**